


Features

- 30mm Barrel Style Housing
- M12 Quick Disconnect
- Driver built in – No External wiring to a driver
- PNP and NPN Strobe input
- Continuous operation or Strobe mode
- Dimmable via built in potentiometer
- Analog intensity via 0-10VDC signal
- Standard optics provide tight focused light



Electrical Input	Voltage - 24 VDC +/- 10% Maximum 6 Watts
Analog Intensity	The output is adjustable from 0-100% of brightness by a 0 -10 VDC signal
Dimmable	The output is manually adjustable from 0-100% of brightness by potentiometer
Continuous Mode	Light will be in continuous mode by leaving signal on strobe input
Strobe	PNP ► +5VDC or greater to activate. NPN ► GND (<1VDC) to activate
Strobe Mode	The Light will operate in either continuous or strobe mode. In strobe mode, the output pulse width will track the pulse width of the strobe pulse.

	<p>1 = 24VDC 2 = NPN STROBE 3 = GND 4 = PNP STROBE 5 = 0-10VDC Analog</p>	<p>Standard M12 mating cable color code:</p> <p>BROWN WHITE BLUE BLACK *GRAY (GREEN/YELLOW)</p>
<p>* 5 pin Standard M12 mating cable must be used: +VDC must be connected to pin 5 if Analog 0-10 VDC is not used.</p>		

S30 – XXX —» Part Number Key

<p>Product Family: Spot Light 30mm Barrel</p>	<p>Color: 625 – Red IR 850nm White – WHI IR 940nm 470 – Blue UV 395nm 505 – Cyan UV 365nm 530 – Green 590 - Yellow</p>
--	---